

DPI Primefact

Benchmarking water productivity of Australian irrigated cotton – 2021 results

December 2022, Primefact PUB22/702, Revised second edition
NSW DPI Water Productivity Benchmarking Team

Summary

Improving water productivity is a high priority for Australian agriculture, especially given increased pressure on available water supplies.

NSW Department Primary Industries (DPI) is working with the Australian cotton industry to improve the productive and sustainable use of irrigation water. NSW DPI, in partnership with the Cotton Research and Development Corporation, has been assessing the trend in water productivity of irrigated cotton since the 1990s.

Latest results from the 2021 season confirm the water productivity of Australian cotton increased from 0.60 bales/ML in 1997 to 1.22 bales/ML in 2021. It ranged from 0.79 to 1.61 bales/ML with the top 20% of growers achieving 1.41 bales/ML or more. The annual rate of productivity improvement was 9% between 1997 and 2007, however it has slowed to 0.3% since 2007. The average water productivity of Australian cotton for 2001 to 2021 is 1.08 bale/ML. This is 2.25 times the global average, based on the latest available data published in 2011.

The Australian industry's average water productivity in 2021 was 30% higher than the maximum achieved in 1997.

Australian cotton water sustainability indicators have improved significantly. The water used to produce one bale of cotton in 2021 was less than half the water used in 1997. The long-term average water consumption in Australia for 2001 to 2021 period was 0.93 ML/bale, which is less than half the global average of 2.07 ML/bale equivalents reported in 2011.

Improvements in Australian water productivity are the result of increased yield, reduced water inputs and increased irrigation efficiency, during a period when rainfall is declining. There is potential for most growers to increase water productivity through improved water management and increased yield.

Establishing water productivity benchmarks

DPI assessed the water productivity and irrigation use efficiency of Australian cotton farms for the 2019 and 2021^[1] seasons. For 2021, we asked 57 cotton growers from across Australia’s major cotton growing areas in Queensland and NSW who participated in previous surveys and a total of 31 responded. Collectively these farms produced 138,156 bales of cotton from an area of 11,748 ha, which represents 5.5% of the irrigated cotton bales produced in Australia, from 5.3% of the country’s total cotton growing area.

Water productivity was assessed using the Gross Production Water Use Index (GPWUI) which is the established method used in the Australian cotton industry. We have continued to use the average GPWUI as the industry benchmark to ensure a valid and consistent presentation of the long-term trends (Tennakoon and Milroy 2003; Williams and Montgomery 2008; Montgomery and Bray 2010; Roth *et al.* 2013; Montgomery *et al.* 2014).

We used grower records of water use to estimate the water balance for each farm, capturing all water inputs and outputs. Details are provided in the standardised measures section below. This data was used to calculate water productivity and water sustainability indices, and irrigation efficiency metrics, as well as to identify where and how much irrigation water is lost, in the irrigated farming system.

Standardised measures

Gross Production Water Use Index (GPWUI) measures how productively water is used. It is the ratio of cotton yield (bales/ha) to all water potentially available for cotton crops (ML/ha) and is expressed as bales/ML (Equation 1). A bale is 227 kg of cotton lint.

$$\text{Equation 1. } GPWUI = \frac{\text{cotton yield}}{\text{irrigation water} + \text{rainfall} + \text{soil moisture change}}$$

Whole Farm Irrigation Efficiency (WFIE) is a measure of how efficiently irrigation water is used (Tennakoon and Milroy 2003). WFIE reflects the proportion of irrigation water used by the crop relative to the total irrigation water on farm (Equation 2).

$$\text{Equation 2. } WFIE = \frac{\text{crop water use} - \text{effective incrop rain} - \text{soil moisture change}}{\text{total irrigation water used on farm}} \times 100$$

A high WFIE value generally reflects low storage, transmission and field losses and that the crop has used a higher proportion of the water brought onto the farm. The WFIE is influenced by rainfall and will be higher in drier years when a greater proportion of crop water needs are met by irrigation.

¹ All years refer to the year the cotton was picked.

The Water Sustainability Index (WSI) is another measure of productivity to indicate how much water is used per unit of product. A smaller index demonstrates more sustainable water use. This index has become increasingly important to cotton buyers and consumers seeking to ensure the product they are purchasing has been produced efficiently (CRDC and CA 2020a,b).

Equation 3.
$$WSI = \frac{\text{irrigation water} + \text{rainfall} - \text{soil moisture change}}{\text{cotton yield}}$$

We express the water sustainability index for irrigated cotton as ML/bale, which is the inverse of the GPWUI equation. Published water use data from most cotton producing countries does not include changes in soil moisture. To enable comparisons with international data, we have not included the soil moisture component in total water inputs in our Australian calculations.

Improvements in water productivity of Australian cotton

The average GPWUI of irrigated cotton has increased by 4% on average annually over 24 years, and by a total of 98% since 1997:

- The average GPWUI has increased from 0.60 bales/ML in 1997 to 1.19 bales/ML in 2018. It further increased to 1.22 bales/ML in 2021 (Figure 1). In 2021, GPWUI ranged from 0.79 to 1.61 bales/ML with the top 20% of growers achieving 1.41 bales/ML or more.
- The annual rate of improvement from 1997 to 2007 was 9% but has slowed since 2007 to 0.3%.
- The average water productivity in 2021 was 30% higher than the maximum productivity achieved in 1997.
- The average GPWUI of 1.22 bales/ML achieved in 2021 demonstrates progress towards the industry target of 1.32 bales/ML by 2023.
- The water productivity achieved by the Australian cotton industry consistently exceeds the global average published in 2011^[2] as demonstrated below:

The average water productivity of Australian cotton between 2001 and 2021 is 1.08 bales/ML or 2.25 times the global average of 0.48 bales/ML equivalent (Mekonnen and Hoekstra 2011).

The average water productivity of Australian cotton for 2001 to 2010 was 0.97 bales/ML and for the 2011 to 2021 period it was 1.17 bales/ML.

² The most recent publicly available global data on cotton lint water consumption was reported in 2011.

- The average GPWUI dropped from 1.19 bales/ML in 2018 to 0.93 bales/ML in 2019. This was due to severe drought requiring greater irrigation water inputs at the same time as cotton yields dropped from 12.38 bales/ha in 2018 to 11.19 bales/ha in 2019 (Figure 2). These drought conditions have affected the rate of long-term improvement in GPWUI. This shows the vulnerability of irrigated cotton to climate change.




Figure 1. GPWUI and WFIE (1997 to 2021 cotton seasons): The blue boxes represent the distribution of GPWUI values in the harvest year the benchmarking occurred. The x in the centre of each blue box is the average GPWUI, the top of the blue box represents the water productivity obtained by the top 25% of growers. The red circles represent WFIE. Data prior to 2019 are redrawn from previous benchmarking (Tennakoon and Milroy 2003; Williams and Montgomery 2008; Montgomery and Bray 2010; Roth et al. 2013; Montgomery et al. 2014).

Irrigation efficiency (WFIE) has improved significantly but can decline in periods of high rainfall:

- WFIE increased from 45% in 1997 to 81% in 2018 (Figure 1).
- However, in the very wet year 2021, which followed severe drought, WFIE fell back to 59%.
- WFIE will decline during very wet seasons (Equation 2) due to increased evaporation and drainage losses that are inherent in wet periods (Figure 4).

These improvements in Australian cotton water productivity are the result of increased yield, reduced water inputs, and increased irrigation efficiency during a period when rainfall is declining (Figure 2).

Benchmarking water productivity of Australian irrigated cotton – 2021 results




Figure 2. Cotton yield, rainfall and irrigation water trends: The trend of rising cotton yields since the 1990s (represented by the yellow dots) has occurred while total growing season rainfall (blue dots) and irrigation water use on farm (black dots) has been trending downwards. Data prior to 2019 are redrawn from previous benchmarking (Tennakoon and Milroy 2003; Williams and Montgomery 2008; Montgomery and Bray 2010; Roth et al. 2013; Montgomery et al. 2014).

The Australian cotton industry demonstrates improvement in the sustainable water use indicator by consuming less water to produce each bale of cotton from 1997 to 2021:

- Long-term water consumption in the Australian cotton industry averaged 0.93 ML/bale between 2002 and 2021, which is less than half the global average of 2.07 ML/bale (Mekonnen and Hoekstra 2011)^[2].
- The cotton water sustainability indicator has improved significantly. In 1997, 1.54 ML was used to produce a bale of cotton, in 2021 this had fallen by 53% to 0.73 ML (Figure 3).
- Water used to produce a bale of cotton lint has reduced significantly since 1985, but the rate of reduction is declining.

Improved irrigation efficiency from 1997 to 2018 is attributed to reduced losses from storages and channels, and improvement in irrigation infrastructure and management. However, during the wet season of 2021, WFIE declined to 59% from 81% in 2018 (Figure 1).

Benchmarking water productivity of Australian irrigated cotton – 2021 results




Figure 3. Change in cotton water sustainability indicator in Australia 1985 to 2021: Projected values for 2025 and 2030 are based on continuation of the current trend. Data prior to 2019 are redrawn from previous benchmarking (Tennakoon & Milroy 2003; Williams & Montgomery 2008; Montgomery & Bray 2010; Roth et al. 2013; Montgomery et al. 2014).




Figure 4. The partitioning of irrigation water into crop use and various on farm losses from 2011, 2018 and in 2021: The proportion of seepage and storage losses doubled from 2018 to 2021 due to a very wet season.

Field application losses increased from 10% in 2011 to 20% during the wetter than normal season of 2021 (Figure 4). Greater losses are probably the result of water being stored longer in dams and channels while growers capitalised on rainfall and soils were wetter for longer periods.

Key messages

- Australian water productivity has doubled over the last 24 years from 0.60 bales/ML in 1997 to 1.22 bales/ML in 2021.
- The annual rate of improvement from 1997 to 2007 was 9% but has slowed since 2007 to 0.3%.
- The industry's average water productivity in 2021 was 30% higher than the maximum achieved in 1997.
- The large range of GPWUI suggests there is significant potential for most growers to increase their water productivity
- The water sustainability indicator has also doubled, with half as much water being used to produce a bale of cotton.
- Improved water productivity and water sustainability are driven by increased yield and reduced water consumption, during a period when rainfall is declining.
- The average water productivity of Australian cotton for the 2001 to 2021 period is 2.25 times the global average identified in 2011^[2].

Future directions

Increasing water productivity continues to be a high priority for the Australian cotton industry. DPI and CRDC will continue to benchmark the water productivity for the Australian cotton industry until at least 2025. Future benchmarking will rely on surveys that are less time consuming for growers and wherever possible utilise data from other sources. The aim is to increase the effectiveness and efficiency of data collection and allow annual benchmarking of water productivity and water sustainability. In addition, benchmarking will also include rain fed cotton systems.

Authors: This DPI Primefact (PUB22/702) was updated with revised information in December 2022 by: Malem McLeod, Research Officer, Tamworth, and Peter Regan, Leader Water Research and Development, Orange

The original 2019 edition of this Primefact (1705) was written by:

David Perović, Research Officer, Narrabri
Ben Crawley, Research and Development Officer, Narrabri
Iain Hume, Research Officer, Wagga Wagga
Robert Hoogers, Research and Development Officer, Yanco
Daowei Sun, Research and Development Officer, Narrabri
Jasim Uddin, Research and Development Officer, Trangie
Peter Regan, Leader Water Research and Development, Orange

References

- CRDC and CA and CRDCa (2020a). Australian Cotton Sustainability Report 2019. Sustainable Australian Cotton Planet. People. Paddock. <https://cottonaustralia.com.au/assets/general/Publications/Sustainability-Reports/2019-Australian-Cotton-Sustainability-Report-Full-Report-2.pdf>
- CRDC and CA (2020b). Australian cotton sustainability targets: Stakeholder consultation report executive summary -December 2020. Sustainable Australian Cotton Planet. People. Paddock. Sustainable Asia Limited. https://www.crdc.com.au/sites/default/files/Targets%20update_summary%20stakeholder%20feedback.pdf
- Mekonnen MM, Hoekstra AY (2011) The green, blue and grey water footprint of crops and derived crop products. *Hydrol. Earth Syst. Sci.* 15(5), 1577-1600.
- Montgomery J, Bray S (2010) Benchmarking water use efficiency in the cotton and grain industries. In '15th Australian Cotton Conference', 2010, Gold Coast. (Sydney).
- Montgomery J, Hoogers B, Shepherd K, Bray S (2014) Water-use efficiency in the Australian Cotton Industry. In '17th Australian Cotton Conference', 5-7 August 2014, Gold Coast, Qld.
- Williams and Montgomery (2008) Bales per megalitre—an industry wide evaluation of the 2006/07 season. 14th Australian Cotton Conference. August 2008, Broadbeach, Queensland.
- Roth G, Harris G, Gillies M, Montgomery J, Wigginton D (2013) Water-use efficiency and productivity trends in Australian irrigated cotton: a review. *Crop and Pasture Science* 64(12), 1033-1048.
- Tennakoon SB, Milroy SP (2003) Crop water use and water use efficiency on irrigated cotton farms in Australia. *Agricultural Water Management* 61(3), 179-194.
-

Acknowledgements

The benchmarking of cotton water productivity is a collaboration between the NSW Department of Primary Industries and the Cotton Research and Development Corporation (project DAN2002).

Thank you to the Cotton Research and Development Corporation, Smarter Irrigation for Profit Phase 2, CottonInfo, Jim Purcell (Aquatech Consulting Pty Ltd), and Janelle Montgomery for their ongoing support for the water productivity benchmarking project. Thanks also to DPI Agriculture Communications Officer, Meg Strang, for editorial support and helping us to clarify the messages in this Primefact.



Copyright and disclaimer statement

© State of New South Wales through Regional NSW 2022. The information contained in this publication is based on knowledge and understanding at the time of writing December 2022. However, because of advances in knowledge, users are reminded of the need to ensure that the information upon which they rely is up to date and to check the currency of the information with the appropriate officer of the Regional NSW or the user's independent adviser.